

Counts for 600 second real-time accumulation										
Distance:	5.12 mm		5.12						Losses	
Rate	SAX	WITH PILE-UP REJECTION		Distance	Center	Val (HW)	An (SW)	HW	Total	
Center	25259758	42099.6 /s		5.12	42099.6	18527.06	18316.12	55.99232	56.49336	
Val (HW)	11116233	18527.06 /s		10.91	15766.33	11972.66	11852.15	24.06182	24.82619	
An (SW)	10989673	18316.12 /s		31.06	2405.297	2310.28	2308.6	3.95031	4.020156	
				70.83	448.8833	445.2217	445.2217	0.815728	0.815728	
				139.6	91.06333	90.825	90.825	0.261723	0.261723	
Distance:	10.91 mm		10.91							
Rate	SAX	WITH PILE-UP REJECTION								
Center	9459797	15766.33 /s								
Val (HW)	7183598	11972.66 /s								
An (SW)	7111290	11852.15 /s								
Distance:	31.06 mm		31.06							
Rate	SAX	WITH PILE-UP REJECTION								
Center	1443178	2405.297 /s								
Val (HW)	1386168	2310.28 /s								
An (SW)	1385160	2308.6 /s								
Distance:	70.83 mm		70.83							
Rate	SAX	WITH PILE-UP REJECTION								
Center	269330	448.8833 /s								
Val (HW)	267133	445.2217 /s								
An (SW)	267133	445.2217 /s								
Distance:	139.6 mm		139.6							
Rate	SAX	WITH PILE-UP REJECTION								
Center	54638	91.06333 /s								
Val (HW)	54495	90.825 /s								
An (SW)	54495	90.825 /s								